STRIVING TOWARD A HIGHER PURPOSE:

High Performance Building in the Land of the Thunder Dragon

Dan Whitmore CPHC, PHIUS Certified Builder Indicator LLC

Cory Hawbecker *AIA, CPHC* Holst Architecture





KARUNA IS THE SANSKRIT WORD FOR COMPASSION

The Karuna Foundation supports visionary organizations in developing nations working to both mitigate carbon emissions and help human populations and the ecosystems they rely on adapt to climate change.




JIGME SINGYE WANGCHUCK SCHOOL OF LAW


Jigme Singye Wangchuck School of Law's mission is to shape young students into lawyers who can navigate the modern global legal environment while remaining mindful of Gross National Happiness and Bhutanese culture and traditions.




DESIGN & TECHNICAL TEAMS JSWL Team Karma Wangchuk Tashi Dorji Karma Karuna Foundation Team Cory Hawbecker Dan Whitmore Sam Hagerman Thorsten Chlupp Galen Staengl













Image: Dan Whitmore



LEGEND
















TRADITIONAL CONSTRUCTION METHODS

- Stone of primary structure
- Heavy timber wood floor and roof framing
- Structural elements are expressive
- Open attic
- Wood shutters, no windows
- No insulation
- No air-sealing
- No mechanical ventilation
- Biomass heating system
- High quality craftsmanship
- Built by Bhutanese





TYPICAL MODERN METHODS


- Reinforced Concrete Frame
- Masonry infill walls with stucco rendering
- Structural elements are disguised
- Open attic (sometimes)
- Site-built single pane wood windows
- No insulation
- No air-sealing
- No mechanical ventilation
- Electric resistance heating
- Low quality craftsmanship
- Built primarily by migrant labor













Air Barrier

- 1. Metal Roof
- 2. Open attic
- 3. Insulated concrete ceiling
- 4. Decorative elements
- 5. Double glazed windows
- 6. Cantilevered floor
- 7. AAC infill wall
- 8. AAC exterior masonry over10 cm mineral wool
- 9. Insulated floor over crawlspace







Building geometry

Enclosed volume:	620,442.9	ft³
Net-volume:	510,518.2	ft³
Total area envelope:	52,254.2	ft²
AV ratio:	0.1	1/ft
Floor area:	42,326.7	ft²

	Air Tightness		Window Performance		Asse	/Btu)		
	cfm/ft ²	ACH50	Avg U-Value (Btu/hr ft ² F)	SHGC	Slab	Below Grade Walls	Walls	Roof
Standard								
Construction								
Partial								
Optimization								
Full								
Optimization		1						

	Air Tightness		Window Performance		Assembly R-Values (hr ft ² F/Btu)			
	cfm/ft ²	ACH50	Avg U-Value (Btu/hr ft ² F)	SHGC	Slab	Below Grade Walls	Walls	Roof
Standard Construction	1.2	7	0.72	0.85	1	2.5	37.5	1
Partial Optimization Full Optimization								

	Air Tightness		Window Performance		Assembly R-Values (hr ft ² F/Btu)			
	cfm/ft ²	ACH50	Avg U-Value (Btu/hr ft ² F)	SHGC	Slab	Below Grade Walls	Walls	Roof
Standard Construction	1.2	7	0.72	0.85	1	2.5	37.5	1
Partial Optimization	0.5	3	0.42	0.6	16	18	59	36.7
Full Optimization								

	Air Tightness		Window Performance		Assembly R-Values (hr ft ² F/Btu)				
	cfm/ft ²	ACH50	Avg U-Value (Btu/hr ft ² F)	SHGC	Slab	Below Grade Walls	Walls	Roof	
Standard Construction	1.2	7	0.72	0.85	1	2.5	37.5	1	
Partial Optimization	0.5	3	0.42	0.6	16	18	59	36.7	
Full Optimization	0.18	1	0.34	0.48	16	18	59	36.7	


	Annual Heating Demand	Heating Load	Site Energy
	kBtu/ft ² yr	Btu/ft ² hr	MWh/yr
Standard Construction	120	38.7	1613
Partial Optimization	38.6	14.4	603
Full Optimization	24	8.1	422


<u>*To Maintain 68°F*</u>



GRAPH: Water Absorption (ASTM C140 - Modified)

GRAPH: Water Vapor Transmission






	CASE	OUTER AAC ENDING MASS % WC	OUTER INSUL RH%		INSUL	INNER AAC ENDING MASS% WC
_	TOP MW 1% DR 3ACH ₅₀	81	100	85	76	1.3
1% DRIVING RAIN	BOTTOM MW 1% DR 3ACH ₅₀	5.2	87	76	72	1.3
DN D	TOP MW 1% DR 2ACH ₅₀	16	94	82	74	1.3
DRIV	BOTTOM MW 1% DR 2ACH ₅₀	4.6	85	75	71	1.3
1% [TOP MW 1% DR 1ACH ₅₀	13.3	94	82	74	1.3
	BOTTOM MW 1% DR 1ACH ₅₀	4.1	81	74	70	1.3

	TOP MW 1% DR 3ACH ₅₀ 5 PERM VR	26.7	97	83	73	1.3
VR	BOTTOM MW 1% DR 3ACH ₅₀ 5 PERM VR	4.8	87	76	72	1.3
	TOP MW 1% DR 2ACH ₅₀ 5 PERM VR	13.4	94	82	74	1.3
PERM	BOTTOM MW 1% DR 2ACH ₅₀ 5 PERM VR	4.2	82	75	71	1.3
5	TOP MW 1% DR 1ACH ₅₀ 5 PERM VR	10.7	93	82	73	1.3
	BOTTOM MW 1% DR 1ACH ₅₀ 5 PERM VR	3.8	81	74	70	1.3













14 = 72235