ICF PASSIVE HOUSE in RIVER FOREST, IL

Post-construction Lessons Learned

■ TOM BASSETT-DILLEY ARCHITECT, LTD.

301 HARRISON STREET OAK PARK, IL 60304

WWW.DRAWINGONPLACE.COM |

ARCHITECT and LEAD CPHC

Tom Bassett-Dilley, CPHC, AIA, President of Passive House Alliance Chicago



GENERAL CONTRACTOR

Brandon Weiss, Graduate Master Builder, PHIUS Cetified Builder, Master Certified Green Professional, LEED-AP, Certified Aging In Place Specialist, Board Member of PHAC



The strength of innovation.

ICF/THERMAL ENVELOPE CONTRACTOR

Eric Barton, CPHC, PHIUS Certified Builder, LEED-AP Homes, Graduate Master Builder, VP of Passive House Alliance Chicago

OUTLINE

- 1. Integrated Design Approach
- 2. Construction and Code
- 3. Certification
- 4. Performance and Use
- 5. Q&A










INTEGRATED DESIGN

- All parties should have goals aligned
 - Discuss objectives
 - Eric and Tom-training
- 2. Start design with Passive House principles
 - PH is a design problem, not an engineering "fix"!
 - Compactness, orientation
- 3. Review key details early
 - Air barrier
 - Windows
 - HVAC
- 4. Continue reviewing (and adjusting if necessary) details during construction



The strength of innovation.








SECOND FLOOR





■ TOM BASSETT-DILLEY ARCHITECT, LTD.

301 HARRISON STREET OAK PARK, IL 60304

WWW.DRAWINGONPLACE.COM





- 1. ICFs
- 2. Slab
- 3. Air barrier detailing
- 4. HVAC
- 5. Windows










CONSTRUCTION ICFs













ICFs/bearing, transitions



21


22

23

24









■ TOM BASSETT-DILLEY ARCHITECT, LTD.

WWW.DRAWINGONPLACE.COM I

301 HARRISON STREET OAK PARK, IL 60304

21. FURRING STRIP SCREW @ 24*
O.C. VERT., 16* O.C. HORIZ.
FASTENMASTER HEADLOK OR EQ.,
VERIFY LENGTH TO PENETRATE
PLASTIC JEP FURRING.

22 WATER-RESISTANT BARRIER-FOIL-FACED POLYISO WITH TAPED SEAMS

25:54 X 1-1/4" LP BASE TRIM 26.STUCCO PARGING 1 28. 3" CLOSED CELL FOAM INSULATION

23. COR-A-VENT 24. FLASHING WITH DRIP EDGE BETWEEN POLYISO LAYERS - LAP OVER STUCCO PARGING





The strength of innovation.

ICFs











CONSTRUCTION Slab









Slab







Air barrier







Air barrier











WWW.DRAWINGONPLACE.COM

301 HARRISON STREET OAK PARK, IL 60304





Air barrier









HVAC













CONSTRUCTION HVAC














CONSTRUCTION HVAC







■ TOM BASSETT-DILLEY ARCHITECT, LTD. ■

301 HARRISON STREET OAK PARK, IL 60304

WWW.DRAWINGONPLACE.COM I



The strength of innovation.

Windows









301 HARRISON STREET OAK PARK, IL 60304

WWW.DRAWINGONPLACE.COM







Windows








THERM calc from Zola: installation psi value .005 BTU/hr. Ft. F












Windows







301 HARRISON STREET OAK PARK, IL 60304

WWW.DRAWINGONPLACE.COM






Windows









301 HARRISON STREET OAK PARK, IL 60304








Exterior









WWW.DRAWINGONPLACE.COM

301 HARRISON STREET OAK PARK, IL 60304





Exterior







301 HARRISON STREET OAK PARK, IL 60304



WWW.DRAWINGONPLACE.COM





Finish










FINISH









301 HARRISON STREET OAK PARK, IL 60304

WWW.DRAWINGONPLACE.COM






The strength of innovation.





301 HARRISON STREET OAK PARK, IL 60304



WWW.DRAWINGONPLACE.COM





CODE

1. Attic hatch


Heat load

13532 BTU/hr

Specific Heating Load P_H / A_{TFA}=

Heating Load P_H


3.8 BTU/hr.ft²







CERTIFICATION

- 1. Start early! PHIUS feedback is key
- 2. Get shading figured out early
- 3. Facilitate communication between PHIUS rater and PHIUS





BEFORE



AFTER





PERFORMANCE

1. Blower door











PERFORMANCE

- 1. Initial temperatures and humidity
- 2. Point source heating and cooling
- 3. Owner training for HVAC



