



**Phius Product Number:** W-101155  
**Date Last Certified:** 08/15/2023  
**THERM Files Available:** Yes

**Phius Certification Path:** Blue Path  
**Valid Through:** 08/15/2025  
**Air Leakage Test Data Available:** No



**PRODUCT INFORMATION**

<b>Product Name:</b> Cascadia Universal Outswing Awning Window	
<b>Manufacturer:</b> Cascadia Windows & Doors	<b>Primary Frame Material:</b> Fiberglass
<b>Series:</b> Universal Series	<b>Fixed or Operable:</b> Operable
<b>Model:</b> Outswing Awning Window	<b>Operation Type:</b> Awning
<b>NFRC CPD #:</b> CWL-K-22-00081-00001	

**IGU DETAILS**

<b>Glazing Name:</b> E366/ Arg/ E180/ Arg/ i89(#6) (6mm) 44,0mm		
<b>Glass Layers:</b> Triple	<b>Gas Fill:</b> Argon	<b>Spacer:</b> Cardinal Endur

**RECOMMENDED CLIMATE ZONES** (NOTE: This information is not for use in building energy models. See next section.)

Recommended Climate Zones and Whole-Window U-values by Zone, at Standard Model Size [Btu/hr·ft <sup>2</sup> ·°F]										
Climate Zone	0, 1, 2	3A	3B	3C	4A, 4B	4C, 5C	5A, 5B	6	7	8
Recommended Zones	✓	✓	✓	✓	✓	✓	✓			
U-Whole-Window	0.15	0.15	0.15	0.15	0.15	0.15	0.15	0.16	0.16	0.16
<b>Modeled Size [W×H]</b>	59.06" × 23.62"		<b>SHGC, Whole Window:</b> 0.13				<b>Condensation Resistance:</b>			

**COMPONENT-LEVEL PERFORMANCE DATA [IP Units]** | Compatible with building energy modeling tools

U-COG   Center of Glass U-Values, by Climate Zone [Btu/hr·ft <sup>2</sup> ·°F]										
Climate Zone	0, 1, 2	3A	3B	3C	4A, 4B	4C, 5C	5A, 5B	6	7	8
U-COG Value	0.10	0.10	0.10	0.10	0.11	0.10	0.11	0.11	0.11	0.11
SHGC-COG   Center of Glass Solar Heat Gain Coefficient, All Climate Zones								0.23		

Frame Parameters	Left Jamb	Right Jamb	Head	Sill
<b>Frame Section</b>	<b>Left</b>	<b>Right</b>	<b>Top</b>	<b>Bottom</b>
<b>Frame Width</b>	4.13"	4.13"	4.13"	4.13"
<b>Frame U-Value</b> [Btu/hr·ft <sup>2</sup> ·°F]	0.20	0.20	0.20	0.20
<b>Glazing-to-Frame Psi Value</b> [Btu/hr·ft·°F]	0.0054	0.0054	0.0057	0.0057
<b>Frame-to-Wall Psi Value</b> is dependent on the on-site installation condition. (See Phius Guidebook for more details.)				



**Phius Product Number:** W-101155  
**Date Last Certified:** 08/15/2023  
**THERM Files Available:** Yes

**Phius Certification Path:** Blue Path  
**Valid Through:** 08/15/2025  
**Air Leakage Test Data Available:** No



**PRODUCT INFORMATION**

<b>Product Name:</b> Cascadia Universal Outswing Awning Window	
<b>Manufacturer:</b> Cascadia Windows & Doors	<b>Primary Frame Material:</b> Fiberglass
<b>Series:</b> Universal Series	<b>Fixed or Operable:</b> Operable
<b>Model:</b> Outswing Awning Window	<b>Operation Type:</b> Awning
<b>NFRC CPD #:</b> CWL-K-22-00081-00001	

**IGU DETAILS**

<b>Glazing Name:</b> E366/ Arg/ E180/ Arg/ i89(#6) (6mm) 44,0mm		
<b>Glass Layers:</b> Triple	<b>Gas Fill:</b> Argon	<b>Spacer:</b> Cardinal Endur

**RECOMMENDED CLIMATE ZONES** (NOTE: This information is not for use in building energy models. See next section.)

Recommended Climate Zones and Whole-Window U-values by Zone, at Standard Model Size [W/m <sup>2</sup> K]										
Climate Zone	0, 1, 2	3A	3B	3C	4A, 4B	4C, 5C	5A, 5B	6	7	8
Recommended Zones	✓	✓	✓	✓	✓	✓	✓			
U-Whole-Window	0.85	0.88	0.88	0.87	0.88	0.88	0.88	0.88	0.89	0.89
Modeled Size [W × H]	1.50 m × 0.60 m		SHGC, Whole Window: 0.13				Condensation Resistance:			

**COMPONENT-LEVEL PERFORMANCE DATA [SI Units]** | Compatible with building energy modeling tools

U-COG   Center of Glass U-Values, by Climate Zone [W/m <sup>2</sup> K]										
Climate Zone	0, 1, 2	3A	3B	3C	4A, 4B	4C, 5C	5A, 5B	6	7	8
U-COG Value	0.56	0.59	0.59	0.59	0.60	0.60	0.60	0.60	0.61	0.62
SHGC-COG   Center of Glass Solar Heat Gain Coefficient, All Climate Zones								0.23		

Frame Parameters	Left Jamb	Right Jamb	Head	Sill
<b>Frame Section</b>	<b>Left</b>	<b>Right</b>	<b>Top</b>	<b>Bottom</b>
<b>Frame Width</b>	105 mm	105 mm	105 mm	105 mm
<b>Frame U-Value [W/m<sup>2</sup>K]</b>	1.14	1.14	1.15	1.15
<b>Glazing-to-Frame Psi Value [W/mK]</b>	0.0095	0.0095	0.01	0.0099
<b>Frame-to-Wall Psi Value</b> is dependent on the on-site installation condition. (See Phius Guidebook for more details.)				