



**Phius Product Number:** W-101736  
**Date Last Certified:** 11/05/2023  
**THERM Files Available:** No

**Phius Certification Path:** Blue Path  
**Valid Through:** 11/05/2025  
**Air Leakage Test Data Available:** No



**PRODUCT INFORMATION**

<b>Product Name:</b> Kommerling USA 88mm Dual Action Window with Foam	
<b>Manufacturer:</b> Kommerling USA	<b>Primary Frame Material:</b> Vinyl
<b>Series:</b> 88mm	<b>Fixed or Operable:</b> Operable
<b>Model:</b> 88mm Dual Action Window with Foam	<b>Operation Type:</b> Dual Action Tilt Turn
<b>NFRC CPD #:</b> KOM-K-9-00213-00001	

**IGU DETAILS**

<b>Glazing Name:</b> Solarban 70 on 6 mm Clear/14.2 mm 90% Argon/6 mm Clear/14.2 mm 90% Argon/Sungate® 400 on Clear 6mm		
<b>Glass Layers:</b> Triple	<b>Gas Fill:</b> Argon	<b>Spacer:</b> HB Fuller Ködispace

**RECOMMENDED CLIMATE ZONES** *(NOTE: This information is not for use in building energy models. See next section.)*

Recommended Climate Zones and Whole-Window U-values by Zone, at Standard Model Size [Btu/hr·ft²·°F]										
Climate Zone	0, 1, 2	3A	3B	3C	4A, 4B	4C, 5C	5A, 5B	6	7	8
Recommended Zones	✓	✓	✓	✓	✓	✓	✓			
U-Whole-Window	0.14	0.14	0.14	0.14	0.14	0.14	0.15	0.15	0.15	0.15
<b>Modeled Size [W×H]</b>	47.24" × 59.06"		<b>SHGC, Whole Window:</b> 0.16				<b>Condensation Resistance:</b>			

**COMPONENT-LEVEL PERFORMANCE DATA [IP Units]** | *Compatible with building energy modeling tools*

U-COG   Center of Glass U-Values, by Climate Zone [Btu/hr·ft²·°F]										
Climate Zone	0, 1, 2	3A	3B	3C	4A, 4B	4C, 5C	5A, 5B	6	7	8
U-COG Value	0.12	0.12	0.12	0.12	0.12	0.12	0.12	0.12	0.13	0.13
SHGC-COG   Center of Glass Solar Heat Gain Coefficient, All Climate Zones								0.24		

Frame Parameters	Left Jamb	Right Jamb	Head	Sill
Frame Section	Left	Right	Top	Bottom
<b>Frame Width</b>	4.65"	4.65"	4.65"	4.65"
<b>Frame U-Value</b> [Btu/hr·ft²·°F]	0.18	0.18	0.17	0.17
<b>Glazing-to-Frame Psi Value</b> [Btu/hr·ft·°F]	0.0097	0.0097	0.0095	0.0095
<b>Frame-to-Wall Psi Value</b> is dependent on the on-site installation condition. <i>(See Phius Guidebook for more details.)</i>				



**Phius Product Number:** W-101736  
**Date Last Certified:** 11/05/2023  
**THERM Files Available:** No

**Phius Certification Path:** Blue Path  
**Valid Through:** 11/05/2025  
**Air Leakage Test Data Available:** No



**PRODUCT INFORMATION**

<b>Product Name:</b> Kommerling USA 88mm Dual Action Window with Foam	
<b>Manufacturer:</b> Kommerling USA	<b>Primary Frame Material:</b> Vinyl
<b>Series:</b> 88mm	<b>Fixed or Operable:</b> Operable
<b>Model:</b> 88mm Dual Action Window with Foam	<b>Operation Type:</b> Dual Action Tilt Turn
<b>NFRC CPD #:</b> KOM-K-9-00213-00001	

**IGU DETAILS**

<b>Glazing Name:</b> Solarban 70 on 6 mm Clear/14.2 mm 90% Argon/6 mm Clear/14.2 mm 90% Argon/Sungate® 400 on Clear 6mm		
<b>Glass Layers:</b> Triple	<b>Gas Fill:</b> Argon	<b>Spacer:</b> HB Fuller Ködispace

**RECOMMENDED CLIMATE ZONES** *(NOTE: This information is not for use in building energy models. See next section.)*

Recommended Climate Zones and Whole-Window U-values by Zone, at Standard Model Size [W/m²K]										
Climate Zone	0, 1, 2	3A	3B	3C	4A, 4B	4C, 5C	5A, 5B	6	7	8
Recommended Zones	✓	✓	✓	✓	✓	✓	✓			
U-Whole-Window	0.82	0.82	0.82	0.82	0.82	0.82	0.82	0.83	0.84	0.86
Modeled Size [W × H]	1.20 m × 1.50 m		SHGC, Whole Window: 0.16				Condensation Resistance:			

**COMPONENT-LEVEL PERFORMANCE DATA [SI Units]** | *Compatible with building energy modeling tools*

U-COG   Center of Glass U-Values, by Climate Zone [W/m²K]										
Climate Zone	0, 1, 2	3A	3B	3C	4A, 4B	4C, 5C	5A, 5B	6	7	8
U-COG Value	0.68	0.68	0.68	0.68	0.68	0.68	0.68	0.69	0.71	0.74
SHGC-COG   Center of Glass Solar Heat Gain Coefficient, All Climate Zones								0.24		

Frame Parameters	Left Jamb	Right Jamb	Head	Sill
<b>Frame Section</b>	<b>Left</b>	<b>Right</b>	<b>Top</b>	<b>Bottom</b>
<b>Frame Width</b>	118 mm	118 mm	118 mm	118 mm
<b>Frame U-Value [W/m²K]</b>	1.00	1.00	0.99	0.99
<b>Glazing-to-Frame Psi Value [W/mK]</b>	0.0168	0.0168	0.0166	0.0166
<b>Frame-to-Wall Psi Value</b> is dependent on the on-site installation condition. <i>(See Phius Guidebook for more details.)</i>				