



**Phius Product Number:** W-101950  
**Date Last Certified:** 02/18/2024  
**THERM Files Available:** No

**Phius Certification Path:** Orange Path  
**Valid Through:** 02/18/2026  
**Air Leakage Test Data Available:** No



PRODUCT INFORMATION		
<b>Product Name:</b> Zola Thermo Plus Alu75 Tilt & Turn		
<b>Manufacturer:</b> Zola Windows	<b>Primary Frame Material:</b> Aluminum	
<b>Series:</b> Thermo Plus Alu75	<b>Fixed or Operable:</b> Operable	
<b>Model:</b> Thermo Plus Alu75 Tilt & Turn	<b>Operation Type:</b> Dual Action Tilt Turn	
IGU DETAILS		
<b>Glazing Name:</b> SN63HT/ARG/EXTRA CLR/ARG/SN63HT		
<b>Glass Layers:</b> Triple	<b>Gas Fill:</b> Argon	<b>Spacer:</b> ALU-PRO MULTITECH G

RECOMMENDED CLIMATE ZONES <i>(NOTE: This information is not for use in building energy models. See next section.)</i>										
Recommended Climate Zones and Whole-Window U-values by Zone, at Standard Model Size [Btu/hr·ft <sup>2</sup> ·°F]										
Climate Zone	0, 1, 2	3A	3B	3C	4A, 4B	4C, 5C	5A, 5B	6	7	8
<b>Recommended Zones</b>	✓	✓	✓	✓	✓	✓	✓			
<b>U-Whole-Window</b>	0.15	0.15	0.15	0.15	0.15	0.15	0.15	0.15	0.16	0.16
<b>Modeled Size [W×H]</b>	47.24" × 59.06"		<b>SHGC, Whole Window:</b> 0.17				<b>Condensation Resistance:</b>			

**COMPONENT-LEVEL PERFORMANCE DATA [IP Units] | Compatible with building energy modeling tools**

U-COG   Center of Glass U-Values, by Climate Zone [Btu/hr·ft <sup>2</sup> ·°F]										
Climate Zone	0, 1, 2	3A	3B	3C	4A, 4B	4C, 5C	5A, 5B	6	7	8
<b>U-COG Value</b>	0.09	0.09	0.09	0.09	0.09	0.09	0.09	0.10	0.11	0.11
<b>SHGC-COG   Center of Glass Solar Heat Gain Coefficient, All Climate Zones</b>								0.24		

Frame Parameters	Left Jamb	Right Jamb	Head	Sill
Frame Section	Left	Right	Top	Bottom
<b>Frame Width</b>	4.21"	4.21"	4.21"	4.21"
<b>Frame U-Value [Btu/hr·ft<sup>2</sup>·°F]</b>	0.25	0.25	0.25	0.25
<b>Glazing-to-Frame Psi Value [Btu/hr·ft<sup>2</sup>·°F]</b>	0.0142	0.0142	0.0142	0.0142

**Frame-to-Wall Psi Value** is dependent on the on-site installation condition. *(See Phius Guidebook for more details.)*



**Phius Product Number:** W-101950  
**Date Last Certified:** 02/18/2024  
**THERM Files Available:** No

**Phius Certification Path:** Orange Path  
**Valid Through:** 02/18/2026  
**Air Leakage Test Data Available:** No



PRODUCT INFORMATION	
<b>Product Name:</b> Zola Thermo Plus Alu75 Tilt & Turn	
<b>Manufacturer:</b> Zola Windows	<b>Primary Frame Material:</b> Aluminum
<b>Series:</b> Thermo Plus Alu75	<b>Fixed or Operable:</b> Operable
<b>Model:</b> Thermo Plus Alu75 Tilt & Turn	<b>Operation Type:</b> Dual Action Tilt Turn

IGU DETAILS		
<b>Glazing Name:</b> SN63HT/ARG/EXTRA CLR/ARG/SN63HT		
<b>Glass Layers:</b> Triple	<b>Gas Fill:</b> Argon	<b>Spacer:</b> ALU-PRO MULTITECH G

RECOMMENDED CLIMATE ZONES <i>(NOTE: This information is not for use in building energy models. See next section.)</i>										
Recommended Climate Zones and Whole-Window U-values by Zone, at Standard Model Size [W/m <sup>2</sup> K]										
Climate Zone	0, 1, 2	3A	3B	3C	4A, 4B	4C, 5C	5A, 5B	6	7	8
<b>Recommended Zones</b>	✓	✓	✓	✓	✓	✓	✓			
<b>U-Whole-Window</b>	0.85	0.84	0.84	0.84	0.84	0.84	0.86	0.87	0.91	0.93
<b>Modeled Size [W x H]</b>	1.20 m x 1.50 m			<b>SHGC, Whole Window:</b> 0.17			<b>Condensation Resistance:</b>			

**COMPONENT-LEVEL PERFORMANCE DATA [SI Units] | Compatible with building energy modeling tools**

U-COG   Center of Glass U-Values, by Climate Zone [W/m <sup>2</sup> K]										
Climate Zone	0, 1, 2	3A	3B	3C	4A, 4B	4C, 5C	5A, 5B	6	7	8
<b>U-COG Value</b>	0.52	0.51	0.51	0.51	0.51	0.51	0.54	0.55	0.61	0.64
<b>SHGC-COG   Center of Glass Solar Heat Gain Coefficient, All Climate Zones</b>								0.24		

Frame Parameters	Left Jamb	Right Jamb	Head	Sill
Frame Section	Left	Right	Top	Bottom
<b>Frame Width</b>	107 mm	107 mm	107 mm	107 mm
<b>Frame U-Value [W/m<sup>2</sup>K]</b>	1.42	1.42	1.42	1.42
<b>Glazing-to-Frame Psi Value [W/mK]</b>	0.0247	0.0247	0.0247	0.0247

**Frame-to-Wall Psi Value** is dependent on the on-site installation condition. *(See Phius Guidebook for more details.)*