



**Phius Product Number:** W-101980  
**Date Last Certified:** 02/18/2024  
**THERM Files Available:** No

**Phius Certification Path:** Orange Path  
**Valid Through:** 02/18/2026  
**Air Leakage Test Data Available:** No



PRODUCT INFORMATION	
<b>Product Name:</b> Zola ThermoPlus uPVC Tilt & Turn	
<b>Manufacturer:</b> Zola Windows	<b>Primary Frame Material:</b> Vinyl
<b>Series:</b> ThermoPlus uPVC	<b>Fixed or Operable:</b> Operable
<b>Model:</b> ThermoPlus uPVC Tilt & Turn	<b>Operation Type:</b> Dual Action Tilt Turn
IGU DETAILS	
<b>Glazing Name:</b> CG PREM2T/ARG/EXTRA CLR/ARG/CG PREM2T	
<b>Glass Layers:</b> Triple	<b>Gas Fill:</b> Argon
<b>Spacer:</b> ALU-PRO MULTITECH G	

RECOMMENDED CLIMATE ZONES <i>(NOTE: This information is not for use in building energy models. See next section.)</i>										
Recommended Climate Zones and Whole-Window U-values by Zone, at Standard Model Size [Btu/hr·ft <sup>2</sup> ·°F]										
Climate Zone	0, 1, 2	3A	3B	3C	4A, 4B	4C, 5C	5A, 5B	6	7	8
Recommended Zones	✓	✓	✓	✓	✓	✓	✓			
U-Whole-Window	0.14	0.14	0.14	0.14	0.14	0.14	0.14	0.14	0.14	0.15
Modeled Size [W×H]	47.24" × 59.06"		SHGC, Whole Window: 0.16				Condensation Resistance:			

**COMPONENT-LEVEL PERFORMANCE DATA [IP Units] | Compatible with building energy modeling tools**

U-COG   Center of Glass U-Values, by Climate Zone [Btu/hr·ft <sup>2</sup> ·°F]										
Climate Zone	0, 1, 2	3A	3B	3C	4A, 4B	4C, 5C	5A, 5B	6	7	8
U-COG Value	0.11	0.10	0.10	0.10	0.10	0.10	0.10	0.10	0.11	0.11
SHGC-COG   Center of Glass Solar Heat Gain Coefficient, All Climate Zones								0.24		

Frame Parameters	Left Jamb	Right Jamb	Head	Sill
Frame Section	Left	Right	Top	Bottom
Frame Width	4.88"	4.88"	4.88"	4.88"
Frame U-Value [Btu/hr·ft <sup>2</sup> ·°F]	0.18	0.18	0.18	0.18
Glazing-to-Frame Psi Value [Btu/hr·ft·°F]	0.0175	0.0175	0.0176	0.0175

**Frame-to-Wall Psi Value** is dependent on the on-site installation condition. *(See Phius Guidebook for more details.)*



**Phius Product Number:** W-101980  
**Date Last Certified:** 02/18/2024  
**THERM Files Available:** No

**Phius Certification Path:** Orange Path  
**Valid Through:** 02/18/2026  
**Air Leakage Test Data Available:** No



PRODUCT INFORMATION		
<b>Product Name:</b> Zola ThermoPlus uPVC Tilt & Turn		
<b>Manufacturer:</b> Zola Windows	<b>Primary Frame Material:</b> Vinyl	
<b>Series:</b> ThermoPlus uPVC	<b>Fixed or Operable:</b> Operable	
<b>Model:</b> ThermoPlus uPVC Tilt & Turn	<b>Operation Type:</b> Dual Action Tilt Turn	
IGU DETAILS		
<b>Glazing Name:</b> CG PREM2T/ARG/EXTRA CLR/ARG/CG PREM2T		
<b>Glass Layers:</b> Triple	<b>Gas Fill:</b> Argon	<b>Spacer:</b> ALU-PRO MULTITECH G

RECOMMENDED CLIMATE ZONES <small>(NOTE: This information is not for use in building energy models. See next section.)</small>										
Recommended Climate Zones and Whole-Window U-values by Zone, at Standard Model Size [W/m <sup>2</sup> K]										
Climate Zone	0, 1, 2	3A	3B	3C	4A, 4B	4C, 5C	5A, 5B	6	7	8
<b>Recommended Zones</b>	✓	✓	✓	✓	✓	✓	✓			
<b>U-Whole-Window</b>	0.81	0.81	0.81	0.81	0.80	0.81	0.80	0.81	0.82	0.83
<b>Modeled Size [W × H]</b>	1.20 m × 1.50 m		<b>SHGC, Whole Window:</b> 0.16				<b>Condensation Resistance:</b>			

**COMPONENT-LEVEL PERFORMANCE DATA [SI Units] | Compatible with building energy modeling tools**

U-COG   Center of Glass U-Values, by Climate Zone [W/m <sup>2</sup> K]										
Climate Zone	0, 1, 2	3A	3B	3C	4A, 4B	4C, 5C	5A, 5B	6	7	8
<b>U-COG Value</b>	0.60	0.59	0.59	0.59	0.58	0.59	0.58	0.59	0.61	0.63
<b>SHGC-COG   Center of Glass Solar Heat Gain Coefficient, All Climate Zones</b>								0.24		

Frame Parameters	Left Jamb	Right Jamb	Head	Sill
Frame Section	Left	Right	Top	Bottom
<b>Frame Width</b>	124 mm	124 mm	124 mm	124 mm
<b>Frame U-Value [W/m<sup>2</sup>K]</b>	1.01	1.01	1.01	1.01
<b>Glazing-to-Frame Psi Value [W/mK]</b>	0.0303	0.0303	0.0305	0.0303

**Frame-to-Wall Psi Value** is dependent on the on-site installation condition. (See Phius Guidebook for more details.)