



**Phius Product Number:** W-102110  
**Date Last Certified:** 09/18/2024  
**THERM Files Available:** No

**Phius Certification Path:** Orange Path  
**Valid Through:** 09/18/2026  
**Air Leakage Test Data Available:** No



PRODUCT INFORMATION	
<b>Product Name:</b> Amberline 76mm Renovation Fixed Window	
<b>Manufacturer:</b> Amberline Windows & Doors	<b>Primary Frame Material:</b> Vinyl
<b>Series:</b> 76mm Renovation	<b>Fixed or Operable:</b> Fixed
<b>Model:</b> 76mm Renovation Fixed Window	<b>Operation Type:</b> Fixed

IGU DETAILS		
<b>Glazing Name:</b> TH 1.0 / TH 1.0		
<b>Glass Layers:</b> Triple	<b>Gas Fill:</b> Argon	<b>Spacer:</b> ALU-PRO MULTITECH G

RECOMMENDED CLIMATE ZONES <i>(NOTE: This information is not for use in building energy models. See next section.)</i>										
Recommended Climate Zones and Whole-Window U-values by Zone, at Standard Model Size [Btu/hr·ft <sup>2</sup> ·°F]										
Climate Zone	0, 1, 2	3A	3B	3C	4A, 4B	4C, 5C	5A, 5B	6	7	8
Recommended Zones				✓	✓	✓	✓			
U-Whole-Window	0.13	0.13	0.13	0.13	0.13	0.13	0.14	0.14	0.14	0.15
Modeled Size [W×H]	47.24" × 59.06"			SHGC, Whole Window: 0.27			Condensation Resistance:			

**COMPONENT-LEVEL PERFORMANCE DATA [IP Units] | Compatible with building energy modeling tools**

U-COG   Center of Glass U-Values, by Climate Zone [Btu/hr·ft <sup>2</sup> ·°F]										
Climate Zone	0, 1, 2	3A	3B	3C	4A, 4B	4C, 5C	5A, 5B	6	7	8
U-COG Value	0.09	0.09	0.09	0.09	0.09	0.09	0.10	0.10	0.11	0.11
SHGC-COG   Center of Glass Solar Heat Gain Coefficient, All Climate Zones								0.35		

Frame Parameters	Left Jamb	Right Jamb	Head	Sill
Frame Section	Left	Right	Top	Bottom
Frame Width	3.31"	3.31"	3.31"	3.31"
Frame U-Value [Btu/hr·ft <sup>2</sup> ·°F]	0.21	0.21	0.21	0.21
Glazing-to-Frame Psi Value [Btu/hr·ft <sup>2</sup> ·°F]	0.0139	0.0139	0.0140	0.0140

**Frame-to-Wall Psi Value** is dependent on the on-site installation condition. *(See Phius Guidebook for more details.)*



**Phius Product Number:** W-102110  
**Date Last Certified:** 09/18/2024  
**THERM Files Available:** No

**Phius Certification Path:** Orange Path  
**Valid Through:** 09/18/2026  
**Air Leakage Test Data Available:** No



PRODUCT INFORMATION	
<b>Product Name:</b> Amberline 76mm Renovation Fixed Window	
<b>Manufacturer:</b> Amberline Windows & Doors	<b>Primary Frame Material:</b> Vinyl
<b>Series:</b> 76mm Renovation	<b>Fixed or Operable:</b> Fixed
<b>Model:</b> 76mm Renovation Fixed Window	<b>Operation Type:</b> Fixed

IGU DETAILS		
<b>Glazing Name:</b> TH 1.0 / TH 1.0		
<b>Glass Layers:</b> Triple	<b>Gas Fill:</b> Argon	<b>Spacer:</b> ALU-PRO MULTITECH G

RECOMMENDED CLIMATE ZONES <i>(NOTE: This information is not for use in building energy models. See next section.)</i>										
Recommended Climate Zones and Whole-Window U-values by Zone, at Standard Model Size [W/m <sup>2</sup> K]										
Climate Zone	0, 1, 2	3A	3B	3C	4A, 4B	4C, 5C	5A, 5B	6	7	8
Recommended Zones				✓	✓	✓	✓			
U-Whole-Window	0.76	0.75	0.75	0.75	0.75	0.75	0.77	0.78	0.82	0.85
Modeled Size [W x H]	1.20 m x 1.50 m		SHGC, Whole Window: 0.27				Condensation Resistance:			

**COMPONENT-LEVEL PERFORMANCE DATA [SI Units] | Compatible with building energy modeling tools**

U-COG   Center of Glass U-Values, by Climate Zone [W/m <sup>2</sup> K]										
Climate Zone	0, 1, 2	3A	3B	3C	4A, 4B	4C, 5C	5A, 5B	6	7	8
U-COG Value	0.53	0.52	0.52	0.52	0.52	0.52	0.55	0.56	0.62	0.65
SHGC-COG   Center of Glass Solar Heat Gain Coefficient, All Climate Zones								0.35		

Frame Parameters	Left Jamb	Right Jamb	Head	Sill
Frame Section	Left	Right	Top	Bottom
Frame Width	84 mm	84 mm	84 mm	84 mm
Frame U-Value [W/m <sup>2</sup> K]	1.21	1.21	1.22	1.22
Glazing-to-Frame Psi Value [W/mK]	0.0242	0.0242	0.0244	0.0244

**Frame-to-Wall Psi Value** is dependent on the on-site installation condition. *(See Phius Guidebook for more details.)*