

Product name:	Zola No Compromise T&T	Center-of-glass properties				
ASHRAE/IECC /DOE North American Climate Zone	North, East, West - facing South-facing		Zola quad hi-g Kr			
Climate specific recommendations:						
Whole-window installed U-value W/m2K BTU/hr.ft2.F						
8		0.67	0.12	Ucog-Value		
7	<input checked="" type="checkbox"/>	0.66	0.12	SHGC W/m2K BTU/hr.ft2.F		
6	<input checked="" type="checkbox"/>	0.64	0.11	0.456 0.366 0.064		
5	<input checked="" type="checkbox"/>	0.64	0.11	0.456 0.346 0.061		
4		0.64	0.11	0.456 0.320 0.056		
Marine North		0.64	0.11	0.456 0.318 0.056		
Marine South	<input checked="" type="checkbox"/>	0.64	0.11	0.456 0.323 0.057		
3	<input checked="" type="checkbox"/>	0.64	0.11	0.456 0.321 0.057		
2 West		0.64	0.11	0.456 0.320 0.056		
2 East		0.64	0.11	0.456 0.320 0.056		
Zola No Compromise T&T						
Swissspacer V	FRAME			Psi-spacer		
	Frame height		U-frame	Ψ		
	mm	in	W/m2K BTU/hr.ft2.F	W/mK BTU/hr.ft.F	W/mK	
Head	115	4.53	0.80 0.14	0.037	0.021	0.139
Sill	115	4.53	0.82 0.15	0.037	0.021	BTU/hr.ft.F
left jamb	115	4.53	0.80 0.14	0.037	0.021	0.080
right jamb	115	4.53	0.80 0.14	0.037	0.021	Grade B

Valid through March 2016