

Product name: **Zola Thermoplus Clad Fixed**



Center-of-glass properties

ASHRAE/IECC
/DOE North
American
Climate Zone

North,
East,
West -
facing

South-
facing

Zola quad hi-g Kr

Climate specific recommendations:	Whole-window installed U-value			Ucog-Value		
	W/m2K	BTU/hr.ft2.F	SHGC	W/m2K	BTU/hr.ft2.F	
8	0.65	0.12	0.456	0.366	0.064	
7	0.64	0.11	0.456	0.346	0.061	<input checked="" type="checkbox"/>
6	0.62	0.11	0.456	0.320	0.056	<input checked="" type="checkbox"/>
5	0.62	0.11	0.456	0.318	0.056	<input checked="" type="checkbox"/>
4	0.62	0.11	0.456	0.319	0.056	
Marine North	0.62	0.11	0.456	0.320	0.056	
Marine South	0.62	0.11	0.456	0.323	0.057	<input checked="" type="checkbox"/>
3	0.62	0.11	0.456	0.321	0.057	<input checked="" type="checkbox"/>
2 West	0.62	0.11	0.456	0.320	0.056	
2 East	0.62	0.11	0.456	0.320	0.056	

Zola Thermoplus Clad Fixed Swissspacer V	FRAME				Psi-spacer		Psi-opaque	
	Frame height		U-frame		Ψ	W/mK	BTU/hr.ft.F	W/mK
	mm	in	W/m2K	BTU/hr.ft2.F				
Head	83	3.27	0.93	0.16	0.031	0.018	0.113	
Sill	83	3.27	0.93	0.16	0.031	0.018	0.113	BTU/hr.ft.F
left jamb	83	3.27	0.93	0.16	0.031	0.018	0.065	
right jamb	83	3.27	0.93	0.16	0.031	0.018	Grade B	

Valid through 2/2016